

#### **FELLING TRAILERS, INC.**

**Product Sheet** 

1525 Main Street South, Sauk Centre, MN 563 Phone: 800-245-2809 - www.felling.com

4500-A

#### FT-100-3 NN-HX

# **Semi - Narrow Neck**

### **GVWR LBS:**

### **GAWR LBS:**

## **WEIGHT LBS:** 13,500


#### **CAPACITY LBS:**

113,500

60,840

100,000

- Swing Clearance is 84" Standard
- 48" King Pin height
- 18" King Pin set back
- · Engineered, Cambered, Fabricated Main Beams
- 8" Structural channel side rails
- Pierced 6" I-Beam crossmembers on 16" centers
- Open Wheel Wells
- Mid-Ship Turn/Marker Lights
- \* NOTE: Dealer must add 12% FET on retail price. Tax is to be calculated & remitted by dealer.





Deck LengthMain Deck Length to Open Wheels TrunnionX18.00FeeFrame TypeChannel Side Rails turned outX1.00StdTrunnion Length49" Axle Spread, Open Wheels TrunnionX12.00FeeBeavertailSelf Cleaning Angle IronX3.00FeeDeck Type6" Jr I-Beam Crossmembers, 16" on CenterX1.00StdDeck TypeWhite Oak 2" NomX0.00StdRamps; Rear24" x 72" Stand Up Self Cleaning W/Spring AssistX1.00PairAppx Deck Height37" Loaded, 39" Unloaded (Open Wheels)X1.00InchWidth102" ODX1.00Inch	ndard & Other Opti	Std. Option St	Std. Qty. Unit
Deck Length         Main Deck Length to Open Wheels Trunnion         X         18.00         Fee           Frame Type         Channel Side Rails turned out         X         1.00         Std           Trunnion Length         49" Axle Spread, Open Wheels Trunnion         X         12.00         Fee           Beavertail         Self Cleaning Angle Iron         X         3.00         Fee           Deck Type         6" Jr I-Beam Crossmembers, 16" on Center         X         1.00         Std           Deck Type         White Oak 2" Nom         X         0.00         Std           Ramps; Rear         24" x 72" Stand Up Self Cleaning W/Spring Assist         X         1.00         Pair           Appx Deck Height         37" Loaded, 39" Unloaded (Open Wheels)         X         1.00         Inch           Width         102" OD         X         1.00         Inch           Tie Downs         D-Rings, 1" ** Bent **         X         14.00         Eac           Brakes         Air, ABS 2S/1M, Meritor WABCO (Parking brakes on all axles)         X         1.00         Std           Axles         25K Oil Bath         X         3.00         Std	nd Capacity 10	X 1.	1.00 Std
Frame Type         Channel Side Rails turned out         X         1.00         Std           Trunnion Length         49" Axle Spread, Open Wheels Trunnion         X         12.00         Fee           Beavertail         Self Cleaning Angle Iron         X         3.00         Fee           Deck Type         6" Jr I-Beam Crossmembers, 16" on Center         X         1.00         Std           Deck Type         White Oak 2" Nom         X         0.00         Std           Ramps; Rear         24" x 72" Stand Up Self Cleaning W/Spring Assist         X         1.00         Pair           Appx Deck Height         37" Loaded, 39" Unloaded (Open Wheels)         X         1.00         Inch           Width         102" OD         X         1.00         Inch           Tie Downs         D-Rings, 1" ** Bent **         X         14.00         Eac           Brakes         Air, ABS 2S/1M, Meritor WABCO (Parking brakes on all axles)         X         1.00         Std           Axles         25K Oil Bath         X         3.00         Std	oseneck N	X 11	11.00 Feet
Trunnion Length         49" Axle Spread, Open Wheels Trunnion         X         12.00         Fee           Beavertail         Self Cleaning Angle Iron         X         3.00         Fee           Deck Type         6" Jr I-Beam Crossmembers, 16" on Center         X         1.00         Std           Deck Type         White Oak 2" Nom         X         0.00         Std           Ramps; Rear         24" x 72" Stand Up Self Cleaning W/Spring Assist         X         1.00         Pair           Appx Deck Height         37" Loaded, 39" Unloaded (Open Wheels)         X         1.00         Inch           Width         102" OD         X         1.00         Inch           Tie Downs         D-Rings, 1" ** Bent **         X         14.00         Eac           Brakes         Air, ABS 2S/1M, Meritor WABCO (Parking brakes on all axles)         X         1.00         Std           Axles         25K Oil Bath         X         3.00         Std	ck Length M	X 18	18.00 Feet
Beavertail         Self Cleaning Angle Iron         X         3.00         Fee           Deck Type         6" Jr I-Beam Crossmembers, 16" on Center         X         1.00         Std           Deck Type         White Oak 2" Nom         X         0.00         Std           Ramps; Rear         24" x 72" Stand Up Self Cleaning W/Spring Assist         X         1.00         Pair           Appx Deck Height         37" Loaded, 39" Unloaded (Open Wheels)         X         1.00         Inch           Width         102" OD         X         1.00         Inch           Tie Downs         D-Rings, 1" ** Bent **         X         14.00         Eac           Brakes         Air, ABS 2S/1M, Meritor WABCO (Parking brakes on all axles)         X         1.00         Std           Axles         25K Oil Bath         X         3.00         Std	me Type C	X 1.	1.00 Std
Deck Type         6" Jr I-Beam Crossmembers, 16" on Center         X         1.00         Std           Deck Type         White Oak 2" Nom         X         0.00         Std           Ramps; Rear         24" x 72" Stand Up Self Cleaning W/Spring Assist         X         1.00         Pair           Appx Deck Height         37" Loaded, 39" Unloaded (Open Wheels)         X         1.00         Inch           Width         102" OD         X         1.00         Inch           Tie Downs         D-Rings, 1" ** Bent **         X         14.00         Eac           Brakes         Air, ABS 2S/1M, Meritor WABCO (Parking brakes on all axles)         X         1.00         Std           Axles         25K Oil Bath         X         3.00         Std	nnion Length 49	X 12	12.00 Feet
Deck Type         White Oak 2" Nom         X         0.00         Std           Ramps; Rear         24" x 72" Stand Up Self Cleaning W/Spring Assist         X         1.00         Pair           Appx Deck Height         37" Loaded, 39" Unloaded (Open Wheels)         X         1.00         Inch           Width         102" OD         X         1.00         Inch           Tie Downs         D-Rings, 1" ** Bent **         X         14.00         Eac           Brakes         Air, ABS 2S/1M, Meritor WABCO (Parking brakes on all axles)         X         1.00         Std           Axles         25K Oil Bath         X         3.00         Std	avertail S	X 3.	3.00 Feet
Ramps; Rear       24" x 72" Stand Up Self Cleaning W/Spring Assist       X       1.00       Pair         Appx Deck Height       37" Loaded, 39" Unloaded (Open Wheels)       X       1.00       Inch         Width       102" OD       X       1.00       Inch         Tie Downs       D-Rings, 1" ** Bent **       X       14.00       Eac         Brakes       Air, ABS 2S/1M, Meritor WABCO (Parking brakes on all axles)       X       1.00       Std         Axles       25K Oil Bath       X       3.00       Std	ck Type 6'	X 1.	1.00 Std
Appx Deck Height         37" Loaded, 39" Unloaded (Open Wheels)         X         1.00         Inch           Width         102" OD         X         1.00         Inch           Tie Downs         D-Rings, 1" ** Bent **         X         14.00         Eac           Brakes         Air, ABS 2S/1M, Meritor WABCO (Parking brakes on all axles)         X         1.00         Std           Axles         25K Oil Bath         X         3.00         Std	ck Type W	X 0.	0.00 Std
Width         102" OD         X         1.00 Inch           Tie Downs         D-Rings, 1" ** Bent **         X         14.00 Eac           Brakes         Air, ABS 2S/1M, Meritor WABCO (Parking brakes on all axles)         X         1.00 Std           Axles         25K Oil Bath         X         3.00 Std	mps; Rear 24	X 1.	1.00 Pair
Tie Downs         D-Rings, 1" ** Bent **         X         14.00         Eac           Brakes         Air, ABS 2S/1M, Meritor WABCO (Parking brakes on all axles)         X         1.00         Std           Axles         25K Oil Bath         X         3.00         Std	ox Deck Height 3	X 1.	1.00 Inches
Brakes Air, ABS 2S/1M, Meritor WABCO (Parking brakes on all axles) X 1.00 Std  Axles 25K Oil Bath X 3.00 Std	ith 10	X 1.	1.00 Inches
Axles 25K Oil Bath X 3.00 Std	Downs D	X 14	14.00 Each
	kes A	es) X 1.	1.00 Std
Suspension 49" Spread, 9700 Hutch X 1.00 Std	es 25	X 3.	3.00 Std
	spension 49	X 1.	1.00 Std
Tires & Wheels 255/70R 22.5 H, 10 Bolt [22.5 x 8.25] Hub Pilot X 12.00 Std	es & Wheels 25	X 12	12.00 Std
Hitch Type Semi King Pin [S] with 18" Setback, 48" Height X 1.00 Std	ch Type S	X 1.	1.00 Std
Jack 200,000# Twin 2 Speed, Holland Mark V (62,500 lb Lift Capacity) X 1.00 Std	k 20	acity) X 1.	1.00 Std
Plug 7 Pole Semi Socket X 1.00 Std	g 7	X 1.	1.00 Std
Lights LED Lights (Peterson), Sealed Wiring Harness (Sealco) X 1.00 Std	hts LI	X 1.	1.00 Std
Trailer Color Felling Black # CCA945378 (White Felling Decal) X 1.00 Std	iler Color Fo	X 1.	1.00 Std
Stripe Color White X 1.00 Std	pe Color W	X 1.	1.00 Std
Standard Document Holder X 1.00 Std	ndard D	X 1.	1.00 Std



### FELLING TRAILERS, INC.

### **Product Sheet** 4500-A

1525 Main Street South, Sauk Centre, MN 563

Y 1.00 Std

Standard	1 step standard in front of the first axle on drivers side	X	1.00	Std
GVWR	113,500 lbs	Χ	1.00	Std