

FELLING TRAILERS, INC.

Product Sheet

1525 Main Street South, Sauk Centre, MN 563 Phone: 800-245-2809 - www.felling.com 4500-A

FT-100-3 NN-LX

Semi - Narrow Neck

GVWR LBS: 113,500

GAWR LBS:


67,500

WEIGHT LBS:

13,500

100,000

- Swing Clearance is 84" Standard
- 48" King Pin height
- 18" King Pin set back
- · Engineered, Cambered, Fabricated Main Beams
- 8" Structural channel side rails
- Pierced 6" I-Beam crossmembers on 16" centers
- Open Wheel Wells
- Mid-Ship Turn/Marker Lights
- * NOTE: Dealer must add 12% FET on retail price. Tax is to be calculated & remitted by dealer.





Standard & Other C	Options Description	Std. Option	Std. Qt	y. Unit
Load Capacity	100,000 lbs Distributed, 75,000 lbs in 16 ft	Х	1.00	Std
Gooseneck	Narrow Neck Design, 84" Swing Clearance	Х	11.00	Feet
Deck Length	Main Deck Length to Open Wheels Trunnion	Х	18.00	Feet
Frame Type	Channel Side Rails turned out	X	1.00	Std
Trunnion Length	49" Axle Spread, Open Wheels Trunnion	X	12.00	Feet
Beavertail	Self Cleaning Angle Iron	Х	3.00	Feet
Deck Type	6" Jr I-Beam Crossmembers, 16" on Center	Х	1.00	Std
Deck Type	White Oak 2" Nom	Х	0.00	Std
Ramps; Rear	24" x 72" Stand Up Self Cleaning W/Spring Assist	Х	1.00	Pair
Appx Deck Height	32" Loaded, 34" Unloaded (Open Wheels)	Х	1.00	Inches
Width	102" OD	Х	1.00	Inches
Tie Downs	D-Rings, 1" ** Bent **	Х	14.00	Each
Brakes	Air, ABS 2S/1M, Meritor WABCO (Parking brakes on all axles)	Х	1.00	Std
Axles	25K Oil Bath	Х	3.00	Std
Suspension	49" Spread, 9700 Hutch	Х	1.00	Std
Tires & Wheels	235/75R 17.5 J, 8 Bolt [17.5 x 6.75] Hub Pilot	Х	12.00	Std
Hitch Type	Semi King Pin [S] with 18" Setback, 48" Height	Χ	1.00	Std
Jack	200,000# Twin 2 Speed, Holland Mark V (62,500 lb Lift Capacity)	Х	1.00	Std
Plug	7 Pole Semi Socket	Х	1.00	Std
Lights	LED Lights (Peterson), Sealed Wiring Harness (Sealco)	Х	1.00	Std
Trailer Color	Felling Black # CCA945378 (White Felling Decal)	Х	1.00	Std
Stripe Color	White	Х	1.00	Std
Standard	Document Holder	Х	1.00	Std



FELLING TRAILERS, INC.

Product Sheet 4500-A

1525 Main Street South, Sauk Centre, MN 563

Y 1.00 Std

Standard	1 step standard in front of the first axle on drivers side	X	1.00	Std			
GVWR	113,500 lbs	Χ	1.00	Std			