



FT-100-3 TSA-L

Tilts - Semi Slide Axle

GVWR LBS:	GAWR LBS:	WEIGHT LBS:	CAPACITY LBS:
122,800	60,000	22,800	100,000

- 48" King Pin height
 - 16" King Pin set back
 - 90° Slope Neck
 - 96" Swing Clearance
 - Engineered, Cambered, Fabricated 1/4" x 14" Main Beams, 3/4" x 6" flanges
 - Engineered, Cambered, Fabricated 1/4" x 16" Side Rails, 1/2" x 3" Flanges
 - Pierced 4" Jr I-Beam crossmembers on 9" centers
 - Lighted Control Panel
 - Roller Grease Bank
 - Hydraulic Tilting Main Deck
 - (2) 6" x 24" Tilt Cylinders
 - (6) 5" Rollers, (2) 4.5" V-rollers and Pad Hydraulic Sliding Axle System
 - Adjustable Beam Scrapers in front of rollers
 - 4.5" Dual Ram Single Stage Slide Axle Cylinder
 - Retracted Slide Axle Cylinder in transport position
 - Knife Edge Approach with Chain Slots
 - Mid-Ship Turn/Marker Lights
 - Hyd Couplers, 3/4" Pioneer, Male 6602-12-12, Female 6601-12-12
- * Subject to FET Tax



Standard & Other Options	Description	Std. Option	Std. Qty.	Unit
Load Capacity	100,000 lbs Distributed, 70,000 lbs in 16 ft	X	1.00	Std
Upper Deck	Upper Deck, 90° Slope	X	11.00	Feet
Deck Length	Tilt Deck Length	X	42.00	Feet
Deck Type	Pierced 4" Jr I-Beam crossmembers on 9" centers	X	1.00	Std
Deck Type	White Oak 2" Nom	X	1.00	Std
Appx Deck Height	39.5" Loaded	X	1.00	Inches
Width	102" OD	X	1.00	Inches
Tie Downs	Combination Chain Slots (3/8") with Stake Pockets every 2'	X	1.00	Std
Brakes	Air, ABS 2S/1M, Meritor WABCO (Parking brakes on all axles)	X	1.00	Std
Axles	25K (1st & 2nd), 25K Heavy Wall (3rd axle), Dexter Oil Bath	X	3.00	Std
Suspension	60" Spread Air Ride, Ridewell 240 with Dump Valve	X	1.00	Axle
Suspension	Pressure gauge for suspension	X	1.00	Std
Tires & Wheels	235/75R 17.5 J, 8 Bolt [17.5 x 6.75] Hub Pilot	X	12.00	Each
Hitch Type	Semi King Pin [S] with 16" Setback, 48" height	X	1.00	Std
Jack	200,000# Twin 2 Speed, Holland Mark V (62,500 lb Lift Capacity) Curb Side Handle	X	1.00	Std
Plug	7 Pole Semi Socket	X	1.00	Std
Lights	LED Lights (Peterson), Sealed Wiring Harness (Sealco)	X	1.00	Std
Lights	Work station light	X	1.00	Std
Trailer Color	Felling Black # CCA945378 (White Felling Decal)	X	1.00	Std
Stripe Color	White	X	1.00	Std



FELLING TRAILERS, INC.

1525 Main Street South, Sauk Centre, MN 563

Phone: 800-245-2809 - www.felling.com

Product Sheet

4500-A

Standard	Winch Mounting Bracket	X	1.00	Std
Standard	Under Carriage Roller Grease Bank	X	1.00	Std
Standard	4.5" Dual Ram Single Stage Slide Cylinder	X	1.00	Std
Standard	Hydraulic Power Up & Down and Slide Axle System	X	1.00	Std
Standard	Tool Box, with Lockable Cover, Curb Side of Gooseneck	X	1.00	Std
Standard	Plumbed for Wet Kit with Hyd Couplers, Pressure- 3/4" Pioneer, Male 6602-12-12, Return- 3/4" Pioneer Female 6601-12-12 ** 3,000 PSI Required **	X	1.00	Std
GVWR	122,800 lbs	X	1.00	Std