

FT-14 PCD

Pole Cargo Dump

GVWR LBS:

16,100

GAWR LBS:

14,000

WEIGHT LBS:

6,000

CAPACITY LBS:

10,100

- Built Per Customer Specs



• Shown with optional removable reel stand & paint



• Shown with optional removable reel stand & paint

Standard & Other Options	Description	Std. Option	Std. Qty.	Unit
Cargo Deck	Hydraulic Dump Bed	X	12.00	Feet
Deck Type	3/16" Smooth Steel	X	1.00	Std
Overall Length	24' Retracted / 40' Extended / 12' Bed	X	24.00	Feet
Width	96" OD x 72" Inside Bed	X	1.00	Inches
Rear Gate	Drop Down Rear Tailgate	X	1.00	Std
Tie Downs	D-Rings, 5/8" Straight, Mounted in Box Corners	X	4.00	Std
Brakes	Electric, Dexter FSA (Fwd Self Adj) On All Axles	X	1.00	Std
Axles	7K Dexter, Straight	X	2.00	Std
Suspension	Dexter Spring **Underslung**	X	1.00	Std
Tires & Wheels	ST235/80R 16 E, 8 Bolt [16 x 6] White Mod	X	4.00	Std
Hitch Type	2.5" Adjustable Lunette Eye/Pintle, [C] 42,000 lb Plate Mount (5/8" Bolt)	X	1.00	Std
Jack	12K Drop Leg Spring Foot ** Side Wind **	X	1.00	Std
Plug	7 Pole RV	X	1.00	Std
Lights	LED,4 tail light system, Sealed Wiring Harness (Tail lights located in rear corner posts)	X	1.00	Std
Lights	All Wiring is Located in the Tongue Traveling in a Heavy Duty Energy Chain No User Intervention is Required of the Wiring when Extending and Retracting the Tongue	X	1.00	Std
Trailer Color	Felling Black # CCA945378 (White Felling Decal)	X	1.00	Std
Stripe Color	White	X	1.00	Std
Standard	3/8" Safety Chains, Grade 70	X	1.00	Std
Standard	36" Winch Bar	X	1.00	Std
Standard	Document Holder	X	1.00	Std
Standard	Heavy Duty Battery, Pump and Remote with 15ft Cord	X	1.00	Std
Standard	Dual Hydraulic Cylinders	X	1.00	Std



FELLING TRAILERS, INC.

1525 Main Street South, Sauk Centre, MN 563

Phone: 800-245-2809 - www.felling.com

Product Sheet

4500-A

Standard	Tread Plate Fenders	X	1.00	Std
Standard	Front Bolster, Adjustable & Removable, 45" Wide Bolster Mounted on Extended Portion of Tongue, Winch Binder & 4"x30' Strap(Located Curb Side)	X	1.00	Std
Standard	Center and Rear Bolsters, 96" Wide Bolsters with 21" Sliding Lever Lock Stanchions with Winch Binder and 30' x 4" Strap (Located Curb Side)	X	1.00	Std
Toolbox	14" Tall X 14" Deep x Full Width Steel Contoured to A-Frame With Side Opening Doors.	X	1.00	Std
GVWR	16,100 lbs	X	1.00	Std