

### FT-16 PCD

### Pole Cargo Dump

**GVWR LBS:**

**18,400**

**GAWR LBS:**

**16,000**

**WEIGHT LBS:**

**5,600**

**CAPACITY LBS:**

**12,800**

- Built Per Customer Specs



• Shown with optional removable reel stand & paint



• Shown with optional removable reel stand & paint

Standard & Other Options	Description	Std. Option	Std. Qty.	Unit
Cargo Deck	Hydraulic Dump Bed	X	12.00	Feet
Deck Type	3/16" Smooth Steel	X	1.00	Std
Overall Length	24' Retracted / 40' Extended / 12' Bed	X	24.00	Feet
Width	102" OD	X	1.00	Inches
Rear Gate	Drop Down Rear Tailgate	X	1.00	Std
Tie Downs	D-Rings, 5/8" Straight, Mounted in Box Corners	X	4.00	Std
Brakes	Electric, Dexter FSA (Fwd Self Adj) On All Axles	X	1.00	Std
Axles	8K Dexter Oil Bath	X	2.00	Std
Suspension	Dexter Spring	X	1.00	Std
Tires & Wheels	215/75R 17.5 H, 8 Bolt [17.5 x 6.75] Plate Wheel	X	4.00	Std
Hitch Type	2.5" Adjustable Lunette Eye/Pintle, [C] 42,000 lb Plate Mount (5/8" Bolt)	X	1.00	Std
Jack	12K Drop Leg Spring Foot ** Side Wind **	X	1.00	Std
Plug	7 Pole RV	X	1.00	Std
Lights	LED,4 tail light system, Sealed Wiring Harness (Tail lights located in rear corner posts)	X	1.00	Std
Lights	All Wiring is Located in the Tongue Traveling in a Heavy Duty Energy Chain No User Intervention is Required of the Wiring when Extending and Retracting the Tongue	X	1.00	Standard
Trailer Color	Felling Black # CCA945378 (White Felling Decal)	X	1.00	Std
Stripe Color	White	X	1.00	Std
Standard	3/8" Safety Chains, Grade 70	X	1.00	Std
Standard	36" Winch Bar	X	1.00	Std
Standard	Document Holder	X	1.00	Std
Standard	Heavy Duty Battery, Pump and Remote with 15ft Cord	X	1.00	Std
Standard	Dual Hydraulic Cylinders	X	1.00	Std



**FELLING TRAILERS, INC.**

1525 Main Street South, Sauk Centre, MN 563

Phone: 800-245-2809 - www.felling.com

*Product Sheet*

4500-A

Standard	Tread Plate Fenders	X	1.00	Std
Standard	Front Bolster, Adjustable & Removable, 45" Wide Bolster Mounted on Extended Portion of Tongue, Winch Binder & 4"x30' Strap(Located Curb Side)	X	1.00	Standard
Standard	Center and Rear Bolsters, 96" Wide Bolsters with 21" Sliding Lever Lock Stanchions with Winch Binder and 30' x 4" Strap (Located Curb Side)	X	1.00	Standard
Toolbox	14" Tall X 14" Deep x Full Width Steel Contoured to A-Frame With Side Opening Doors.	X	1.00	Std
GVWR	18,400 lbs	X	1.00	Std