


FT-30-2 LP Drill Series

Deckover LP Drill Series

GVWR LBS:	GAWR LBS:	WEIGHT LBS:	CAPACITY LBS:
37,600	30,000	7,600	30,000

- Engineered, Cambered, Fabricated 14" Main Beams
- 4" pierced High Tensile Jr I-Beam crossmembers 16" o.c.
- 7" channel side rails, flat side out
- Tread Plate covered wheels
- * NOTE: Dealer must add 12% FET on retail price. Tax is to be calculated & remitted by dealer.



• Shown with optional air ramps and paint.

Standard & Other Options	Description	Std. Option	Std. Qty.	Unit
Deck Length	Main Deck Length (Pierced Frame)	X	20.00	Feet
Beavertail	Self Cleaning 5" x 3" Angle Iron Beavertail	X	6.00	Feet
Beavertail, Acc	Double Incline	X	1.00	Std
Deck Type	White Oak 2" Nom	X	1.00	Std
Ramps; Rear	6' x 20" Self Cleaning 5" X 3" Angle Iron, Spring Assist	X	1.00	Pair
Appx Deck Height	33" Loaded, 35" Unloaded	X	1.00	Inches
Width	102" OD	X	1.00	Inches
Tie Downs	D-Rings, 1" ** Straight ** (One Set Centered on BVT)	X	12.00	Each
Brakes	Electric, Dexter FSA (Fwd Self Adj) On All Axles	X	1.00	Std
Axles	15K Dexter Oil Bath	X	2.00	Axles
Suspension	25,000 lb Heavy Duty 3 leaf springs, for Hutch 9700	X	2.00	Axle
Suspension	49" Spread (Spring), 9700 Hutch	X	1.00	Std
Tires & Wheels	215/75R 17.5 H, 8 Bolt [17.5 x 6.75] Hub Pilot	X	8.00	Std
Hitch Length	Center of Coupler to Headboard, Appx	X	6.30	Feet
Hitch Type	3" Adjustable Lunette Eye/Pintle, [C] 66,000 lb Plate Mount (3/4" Bolt)	X	1.00	Std
Jack	140,000 lb Twin 2 Speed (39,000 lb Lift Capacity)	X	1.00	Pair
Plug	7 Pole RV	X	1.00	Std
Lights	LED Lights (Peterson), Sealed Wiring Harness (Sealco)	X	1.00	Std
Trailer Color	Felling Black # CCA945378 (White Felling Decal)	X	1.00	Std
Stripe Color	White	X	1.00	Std
Standard	1/2" Safety Chains, Grade 70	X	1.00	Std
Standard	2 Steps, 1 on the Standard Hitch and 1 in front of Axles on Roadside	X	2.00	Std
Standard	Document Holder	X	1.00	Std



FELLING TRAILERS, INC.

Product Sheet

1525 Main Street South, Sauk Centre, MN 563

4500-A

Phone: 800-245-2809; FAX: 320-352-5230

www.felling.com

Standard	Toolbox, Extended as far forward as possible (with paddle latch) in a-frame area of hitch	X	1.00	Std
GVWR	37,600 lbs	X	1.00	Std