


### FT-6 R

### Reel

<b>GVWR LBS:</b>	<b>GAWR LBS:</b>	<b>WEIGHT LBS:</b>	<b>CAPACITY LBS:</b>
<b>8,000</b>	<b>7,000</b>	<b>1,920</b>	<b>6,080</b>

- Built Per Customer Specs
- 5" X 3" X 1/4" tube uprights
- Electric/ Hydraulic Power Up & Down



Standard & Other Options	Description	Std. Option	Std. Qty.	Unit
Reel Capacity	Capacity for a 120" X 60" Reel, 2.25" shaft	X	1.00	Inches
Reel Capacity	Reel Diameter at lowest position, 24" Reel	X	1.00	Std
Overall Length	Overall Length	X	12.00	Feet
Width	93" OD, 60.5" ID	X	1.00	Inches
Brakes	Electric, Dexter FSA (Fwd Self Adj) On All Axles	X	1.00	Std
Axles	7K Axle Stubs	X	1.00	Std
Tires & Wheels	ST235/80R 16 E, 8 Bolt [16 x 6] White Mod	X	2.00	Std
Hitch Type	3" Adjustable Lunette Eye/Pintle, [C] 25,000 lb, Channel Mount (5/8" Bolt)	X	1.00	Std
Jack	7K Drop Leg ** Top Wind **	X	1.00	Std
Plug	7 Pole RV	X	1.00	Std
Lights	LED Lights (Peterson), Sealed Wiring Harness (Sealco)	X	1.00	Std
Trailer Color	Felling Black # CCA945378 (White Felling Decal)	X	1.00	Std
Stripe Color	White	X	1.00	Std
Standard	3/8" Safety Chains, Grade 70	X	1.00	Std
Standard	Elec/Hydraulic Pump with 12 V battery in Lockable Enclosure	X	1.00	Std
GVWR	8,000 lbs	X	1.00	Std