

## **FELLING TRAILERS, INC.**

**Product Sheet** 

1525 Main Street South, Sauk Centre, MN 563 Phone: 800-245-2809; FAX: 320-352-5230

www.felling.com

## **FT-80-3 NN-HX**

## **GAWR LBS:**

92,500 60,840 **WEIGHT LBS:** 

**CAPACITY LBS:** 

80,000


12,500

- Swing Clearance is 84" Standard • 8" Structural channel side rails 48" King Pin height
  - Pierced 6" I-Beam crossmembers on 16" centers
  - Open Wheel Wells

**Semi - Narrow Neck** 

- NOTE: Dealer must add 12% FET on retail price. Tax is to be calculated & remitted by dealer.
- 18" King Pin set back • Engineered, Cambered, Fabricated Main Beams

**GVWR LBS:** 



Load Capacity 80,000 lbs Distributed, 60,0  Gooseneck Narrow Neck Design, 84" S	0 lbs in 16 ft	Х	1.00	
Gooseneck Narrow Neck Design, 84" S			1.00	std
	ving Clearance	Х	11.00	Feet
Deck Length Main Deck Length to Open	Vheels Trunnion	Х	18.00	Feet
Frame Type Channel Side Rails turned of	ut	Х	1.00	Std
Trunnion Length 49" Axle Spread, Open Whe	els Trunnion	Х	12.00	Feet
Beavertail Self Cleaning Angle Iron		Х	3.00	Feet
Deck Type 6" Jr I-Beam Crossmembers	, 16" on Center	Х	1.00	Std
Deck Type White Oak 2" Nom		Х	0.00	Std
Ramps; Rear 24" x 72" Stand Up Self Cle	ning W/Spring Assist	Х	1.00	Pair
Appx Deck Height 37" Loaded, 39" Unloaded (	Open Wheels)	Х	1.00	Inches
Width 102" OD		Х	1.00	Inches
Tie Downs D-Rings, 1" ** Bent **		Х	14.00	Each
Brakes Air, ABS 2S/1M, Meritor WA	BCO (Parking brakes on all axles)	Х	1.00	Std
Axles 25K Oil Bath		Х	3.00	Std
Suspension 49" Spread, 9700 Hutch		Х	1.00	Std
Tires & Wheels 255/70R 22.5 H, 10 Bolt [22	5 x 8.25] Hub Pilot	Х	12.00	Std
Hitch Type Semi King Pin [S] with 18" S	etback, 48" Height	Х	1.00	Std
Jack 200,000# Twin 2 Speed, Ho	land Mark V (62,500 lb Lift Capacity)	Х	1.00	Std
Plug 7 Pole Semi Socket		Х	1.00	Std
Lights LED Lights (Peterson), Sea	ed Wiring Harness (Sealco)	Х	1.00	Std
Trailer Color Felling Black # CCA945378	(White Felling Decal)	Χ	1.00	Std
Stripe Color White		Х	1.00	Std
Standard Document Holder		Х	1.00	Std



## **FELLING TRAILERS, INC.**

**Product Sheet** 

1525 Main Street South, Sauk Centre, MN 563 Phone: 800-245-2809; FAX: 320-352-5230

4500-A www.felling.com

Standard 1 step standard in front of the first axle on drivers side X 1.00 Std

GVWR 92,500 lbs X 1.00 Std