



ISO 9001 Quality Management System | WBENC-Certified WBE | THE TRAILER EXPERTS - SINCE 1974

Product Sheet

Felling Trailers, Inc. 2021

www.felling.com • 1-800-245-2809

1525 Main Street South

Sauk Centre, MN 56378

FT-14 I DS		I-Series Drill	
GVWR LBS: 16,100	GAWR LBS: 7,000	WEIGHT LBS: 3,940	CAPACITY LBS: 12,160

Feature Name	Standard Features	Std. Qty	UOM
Model	FT-14 I DS	1	
Frame Type	3" Angle Lip Up	1	Std
Deck Length	Add Deck Length	16	Feet
Deck Type	White Oak 2" Nom	1	Std
Dovetail	Dovetail Length, Wood Inlay	3	Feet
Ramps; Rear	6' x 16" Angle Iron Spring Assist	1	Pair
Ramps, Acc	Mount Ramps to Road Side with Hold-Up Anchor in Floor and Full Width Ramp Rod (verify center ramp position before install)	1	Std
Appx Deck Height	21" Loaded, 24" Unloaded	1	Inches
Width	102" OD, 82" ID	1	Std
Tie Downs	D-Rings, 5/8" Straight, (2) 45° top of deck in corners, (1) centered on front of deck, (2) front of fenders, (2) rear of deck, (2) 1/2 way on BVT, (1) offset on BVT deck	10	Std
Brakes	Electric, FSA (Fwd Self Adj) On All Axles	1	Std
Axles	7K Heavy Duty, Drop	2	Std
Axles, Acc	EZ-Lube Hubs	1	Std
Hitch Height	Approximate Adjustment Hitch Range 13.5" to 22.5" (20" to 24.5" if Hyd)	1	Std
Hitch Length	Center of Coupler to Headboard, Appx - Adj Hitch Range 13.5" to 22.5" (20" to 24.5" if Hyd)	5	Feet
Hitch Type	2.5" Adjustable Lunette Eye/Pintle, [C] 42,000 lb Plate Mount (5/8" Bolt)	1	Std
Jack	12K w/ Spring Loaded Drop Leg, Side Wind	1	Std
Lights	LED, 4 tail light system, Sealed Wiring Harness	1	Std
Plug	7 Pole RV	1	Std
Suspension	Spring, 36" Spread	1	Std
Tires & Wheels	215/75R 17.5 H, 8 Bolt [17.5 x 6.75] Plate Wheel	4	Each
Trailer Color	Felling Black # CCA945378 (White Felling Decal)	1	Std
Standard	3/8" Safety Chains, Grade 70	1	Std
Standard	Document Holder	1	Std
Standard	Drill Kit Ready - Steel Mounting Strips Under Deck To Mount Tank	1	Std
GVWR	16,100 lbs	1	Std