



ISO 9001 Quality Management System | WBENC-Certified WBE | THE TRAILER EXPERTS - SINCE 1974

Product Sheet

Felling Trailers, Inc. 2021

www.felling.com • 1-800-245-2809

1525 Main Street South

Sauk Centre, MN 56378

| | |
|------------------|---------------------------------|
| FT-14 SLR | Self Loading Reel Series |
|------------------|---------------------------------|

GVWR LBS: 16,100

GAWR LBS: 14,000

WEIGHT LBS: 4,265

CAPACITY LBS: 11,835



| Feature Name | Standard Features | Std. Qty | UOM |
|---------------------------|--|----------|------|
| Model | FT-14 SLR | 1 | |
| Frame Type | 8" x 2" x .25" Tube | 1 | Std |
| Overall Length | Overall Length in Feet | 15.5 | Feet |
| Reel Bar | 2 7/8" x 3/8" Wall Tube With Crossarm and Locking Collar | 1 | Std |
| Reel Bar | SAE 660 Bronze Reel Bar Saddle | 1 | Std |
| Reel Capacity | Capacity for up to a 120"(H) X 70"(W) Reel - 48" Minimum Reel Diameter | 1 | Std |
| Width | 102" OD, 71" ID | 1 | Std |
| Brakes | Electric, FSA (Fwd Self Adj) On All Axles | 1 | Std |
| Axles | 7K | 2 | Std |
| Axles, Acc | EZ-Lube Hubs | 1 | Std |
| Suspension | Rubber Torsion | 1 | Opt |
| Tires & Wheels | ST235/80R 16 E, 8 Bolt [16 x 6] Mod | 4 | Each |
| Hitch Type | 3" Adjustable Lunette Eye/Pintle, [C] 50,000 lb Plate Mount (5/8" Bolt) | 1 | Std |
| Jack | 12K w/ Spring Loaded Drop Leg, Side Wind | 1 | Std |
| Stabilizer Jack | Rear Pivoting Hydraulic Stabilizer Frame Jacks | 1 | Pair |
| Lights | LED, 4 tail light system, Sealed Wiring Harness | 1 | Std |
| Plug | 7 Pole RV | 1 | Std |
| Trailer Color | Felling Black # CCA945378 (White Felling Decal) | 1 | Std |
| Standard | 3/8" Safety Chains, Grade 70 | 1 | Std |
| Standard | Document Holder | 1 | Std |
| Option | HYD Retriever/Take up, Direct Connection to Reel Bar | 1 | Std |
| Option | Self-Contained Hydraulic Power Pack -13 HP Gas Engine Includes Enclosure | 1 | Std |
| GVWR | 16,100 lbs | 1 | Std |