

Product Sheet

Felling Trailers, Inc. 2025

www.felling.com • 1-800-245-2809

1525 Main Street South

Sauk Centre, MN 56378

FT-16 DDI DS

Drop Deck I Drill Series

GVWR LBS: 18,400

GAWR LBS: 16,000

WEIGHT LBS: 4,545

CAPACITY LBS: 13,855



Feature Name	Standard Features	Std. Qty	UOM
Model	FT-16 DDI DS	1	
Frame Type	3" Angle Lip Up	1	Std
Deck Length	Add Deck Length	18	Feet
Deck Type	White Oak 2" Nom	1	Std
Dovetail	Dovetail Length, Wood Inlay	3	Feet
Ramps; Rear	6' x 16" Angle Iron Spring Assist (4" Channel - Maximum 10,000lb. Axle Load Per Ramp Pair)	1	Pair
Ramps, Acc	Mount Ramps to Road Side with Hold-Up Anchor in Floor and Full Width Ramp Rod (verify center ramp position before install)	1	Std
Appx Deck Height	25" Loaded, 26" Unloaded	1	Inches
Width	102" OD, 83" ID	1	Std
Tie Downs	D-Rings, 5/8" Straight, (2) 45° top of deck in corners, (1) centered on front of deck (Bolt On), (2) front of fenders, (2) rear of deck, (2) 1/2 way on BVT, (1) offset on BVT deck	10	Std
Brakes	Electric, FSA (Fwd Self Adj) On All Axles	1	Std
Axles	8K Oil Bath Drop	2	Std
Suspension	Spring, 36" Spread	1	Std
Tires & Wheels	215/75R 17.5 H, 8 Bolt [17.5 x 6.75] Plate Wheel	4	Each
Hitch Height	Approximate Adjustment Hitch Range - 16" Bottom / 25" Top Electric Brakes (Hyd Surge Brakes 24" Bottom / 29" Top) Based on unladen, level trailer	1	Std
Hitch Length	Center of Coupler to Headboard, Appx	5	Feet
Hitch Type	2.5" Adjustable Lunette Eye/Pintle, [C] 42,000 lb Plate Mount (5/8" Bolt)	1	Std
Jack	12K w/ Spring Loaded Drop Leg, Side Wind	1	Std
Lights	LED, 4 tail light system, Sealed Wiring Harness	1	Std
Plug	7 Pole RV	1	Std
Trailer Color	Felling Black # CCA945378 (White Felling Decal)	1	Std
Standard	3/8" Safety Chains, Grade 70	1	Std
Standard	Document Holder	1	Std
Standard	Drill Kit Ready - Steel Mounting Strips Under Deck To Mount Tank	1	Std
GVWR	18,400 lbs	1	Std