



ISO 9001 Quality Management System | WBENC-Certified WBE | THE TRAILER EXPERTS - SINCE 1974

Product Sheet

Felling Trailers, Inc. 2021

www.felling.com • 1-800-245-2809

1525 Main Street South

Sauk Centre, MN 56378

FT-24 I DS		I-Series Drill	
GVWR LBS: 25,980	GAWR LBS: 12,000	WEIGHT LBS: 5,275	CAPACITY LBS: 25,980

Feature Name	Standard Features	Std. Qty	UOM
Model	FT-24 I DS	1	
Frame Type	3" Angle Lip Up	1	Std
Deck Type	White Oak 2" Nom	1	Std
Dovetail	Dovetail Length, Wood Inlay	3	Feet
Ramps; Rear	6' x 16" Angle Iron Spring Assist	1	Pair
Ramps, Acc	Mount Ramps to Road Side with Hold-Up Anchor in Floor and Full Width Ramp Rod (verify center ramp position before install)	1	Std
Appx Deck Height	24" Loaded, 26" Unloaded (Torsion)	1	Inches
Width	102" OD, 82" ID	1	Std
Brakes	Electric, FSA (Fwd Self Adj) On All Axles	1	Std
Axles	12K Oil Bath	2	Std
Hitch Height	Approximate Adjustment Hitch Range 14" to 23" (22" to 27" if Hyd)	1	Std
Hitch Type	3" Adjustable Lunette Eye/Pintle, [C] 50,000 lb Plate Mount (5/8" Bolt)	1	Std
Jack	12K w/ Spring Loaded Drop Leg, Side Wind	1	Std
Lights	LED, 4 tail light system, Sealed Wiring Harness	1	Std
Plug	7 Pole RV	1	Std
Suspension	Rubber Torsion, 42" Spread	1	Std
Tires & Wheels	235/75R 17.5 J, 8 Bolt [17.5 x 6.75] Plate Wheel	4	Each
Trailer Color	Felling Black # CCA945378 (White Felling Decal)	1	Std
Standard	1/2" Safety Chains, Grade 70	1	Std
Standard	Document Holder	1	Std
Standard	Drill Kit Ready - Steel Mounting Strips Under Deck To Mount Tank	1	Std
GVWR	25,980 lbs	1	Std