



ISO 9001 Quality Management System | WBENC-Certified WBE | THE TRAILER EXPERTS - SINCE 1974

**Product Sheet**

Felling Trailers, Inc. 2021

www.felling.com • 1-800-245-2809

1525 Main Street South

Sauk Centre, MN 56378

<b>FT-30-2 LP Drill Series</b>		<b>Low Pro Drill Series</b>	
<b>GVWR LBS: 37,600</b>	<b>GAWR LBS: 15,000</b>	<b>WEIGHT LBS: 8,600</b>	<b>CAPACITY LBS: 29,000</b>

Feature Name	Standard Features	Std. Qty	UOM
<b>Model</b>	<b>FT-30-2 LP Drill Series</b>	1	
<b>Frame Type</b>	Engineered Fabricated High Tensile Main Frame Beams With Pierced Junior I-Beams Crossmembers	1	Std
<b>Deck Length</b>	Add Deck Length	20	Feet
<b>Deck Type</b>	White Oak 2" Nom	1	Std
<b>Beavertail</b>	Self Cleaning 5" x 3" Angle Iron Beavertail	6	Feet
<b>Beavertail, Acc</b>	Double Incline	1	Std
<b>Ramps; Rear</b>	6' x 20" Self Cleaning 5" X 3" Angle Iron, Spring Assist	1	Pair
<b>Appx Deck Height</b>	33" Loaded, 35" Unloaded	1	Inches
<b>Width</b>	102" OD	26	Feet
<b>Tie Downs</b>	D-Rings, 1" ** Straight ** (One Set Centered on BVT)	12	Each
<b>Brakes</b>	Electric, FSA (Fwd Self Adj) On All Axles	1	Std
<b>Axles</b>	15K Oil Bath	2	Std
<b>Suspension</b>	25,000 lb Heavy Duty 3 leaf springs, for Hutch 9700	2	Axle
<b>Suspension</b>	49" Spread (Spring), 9700 Hutch	1	Std
<b>Tires &amp; Wheels</b>	215/75R 17.5 H, 8 Bolt [17.5 x 6.75] Hub Pilot	8	Std
<b>Hitch Length</b>	Center of Coupler to Headboard, Appx	6.3	Feet
<b>Hitch Type</b>	3" Adjustable Lunette Eye/Pintle, [C] 66,000 lb Plate Mount (3/4" Bolt)	1	Std
<b>Jack</b>	140,000 lb Twin 2 Speed (39,000 lb Lift Capacity)	1	Pair
<b>Lights</b>	LED Lights (Peterson), Sealed Wiring Harness (Sealco)	1	Std
<b>Plug</b>	7 Pole RV	1	Std
<b>Trailer Color</b>	Felling Black # CCA945378 (White Felling Decal)	1	Std
<b>Stripe Color</b>	White	1	Std
<b>Standard</b>	Document Holder	1	Std
<b>Standard</b>	Toolbox, Extended as far forward as possible (with lockable latch) in a-frame area of hitch	1	Std
<b>Standard</b>	2 Steps, 1 on the Standard Hitch and 1 in front of Axles on Roadside	2	Std
<b>Standard</b>	1/2" Safety Chains, Grade 70	1	Std
<b>GVWR</b>	37,600 lbs	1	Std