



ISO 9001 Quality Management System | WBENC-Certified WBE | THE TRAILER EXPERTS - SINCE 1974

**Product Sheet**

Felling Trailers, Inc. 2021

www.felling.com • 1-800-245-2809

1525 Main Street South

Sauk Centre, MN 56378

<b>FT-45-2 LP Limited</b>		<b>Deck Over LP Limited Series</b>	
<b>GVWR LBS: 54,400</b>	<b>GAWR LBS: 54,400</b>	<b>WEIGHT LBS: 9,400</b>	<b>CAPACITY LBS: 45,000</b>

Feature Name	Standard Features	Std. Qty	UOM
<b>Model</b>	<b>FT-45-2 LP Limited</b>	1	
<b>Frame Type</b>	Engineered Fabricated Hi-Tensile Grade 80 Main Frame Beams with Grade 80 Jr-I Cross-Members	1	Std
<b>Frame Type</b>	8" Channel Side Rails, Flanges In	1	Std
<b>Frame Type</b>	4" High Tensile Jr I-Beam Crossmembers 12" On Center	1	Std
<b>Deck Length</b>	Add Main Deck Length (Pierced Frame)	20	Feet
<b>Deck Type</b>	Apitong, 1 3/8" ** Decking must sit above side rails 1/4" minimum **	1	Std
<b>Beavertail</b>	Wood Inlaid Beavertail (Apitong)	6	Feet
<b>Beavertail, Acc</b>	Double Incline	1	Opt
<b>Ramps; Rear</b>	6' x 20" Wood Inlaid Spring Assist (Apitong)	1	Pair
<b>Appx Deck Height</b>	33" Loaded, 35" Unloaded	1	Inches
<b>Width</b>	102" OD	26	Feet
<b>Tie Downs</b>	D-Rings, 1" ** Straight ** (One Set Centered on BVT)	14	Each
<b>Brakes</b>	Air, ABS 2S/1M, (Parking brakes on all axles)	1	Each
<b>Axles</b>	25K Oil Bath	2	Std
<b>Suspension</b>	25,000 lb Heavy Duty 3 Leaf Springs	1	Std
<b>Suspension</b>	49" Spread (Spring), 9700 Hutch	1	Std
<b>Tires &amp; Wheels</b>	235/75R 17.5 J, 8 Bolt [17.5 x 6.75] Hub Pilot	8	Std
<b>Hitch Length</b>	Center of Coupler to Headboard, Appx	6.3	Feet
<b>Hitch Type</b>	3" Adjustable Lunette Eye/Pintle, [C] 66,000 lb Plate Mount (3/4" Bolt)	1	Std
<b>Jack</b>	140,000 lb Twin 2 Speed (39,000 lb Lift Capacity)	1	Pair
<b>Lights</b>	LED Lights (Peterson), Sealed Wiring Harness (Sealco)	1	Std
<b>Plug</b>	7 Pole Semi	1	Std
<b>Trailer Color</b>	Felling Black # CCA945378 (White Felling Decal)	1	Std
<b>Stripe Color</b>	White	1	Std
<b>Standard</b>	1/2" Safety Chains, Grade 70	1	Std
<b>Standard</b>	Large Lockable Toolbox in Hitch A-Frame	1	Std
<b>Standard</b>	Document Holder	1	Std
<b>Standard</b>	3 Steps, 1 Drivers Side on the hitch and 1 in each side ahead of the axles	3	Std
<b>GVWR</b>	54,400 lbs	1	Std