Product Sheet Felling Trailers, Inc. 2025

1525 Main Street South Sauk Centre, MN 56378

www.felling.com • 1-800-245-2809

FT-50-3 LP Paver Paver Series

GVWR LBS: 63,000 GAWR LBS: 22,500 WEIGHT LBS: 14,800 CAPACITY LBS: 48,200

Feature Name	Standard Features	Std. Qty	UOM
Model	FT-50-3 LP Paver	1	
	Engineered Fabricated Hi-Tensile Grade 80 Main Frame Beams with Grade 80		
Frame Type	Jr-I Cross-Members	1	Std
Deck Length	Add Main Deck Length (Pierced Frame)	28	Feet
Deck Type	White Oak 2" Nom	1	Std
Beavertail	Wood Inlaid Beavertail	6	Feet
Beavertail, Acc	Double Incline Double Incline	1	Opt
Appx Deck Height	33"Loaded, 35" Unloaded	1	Inches
	45" Wide x 11' (7.5'+3.5') Bi-Fold, Air Operated, Wood Inlaid (Includes 3 large		
Ramps; Rear	air tanks & Bolt on Ramp Legs)	1	Pair
Width	102"OD	32	Feet
Tie Downs	D-Rings, 1" ** Straight ** (One Set Centered on BVT)	20	Each
Brakes	Air, ABS 2S/1M, (Parking brakes on all axles)	1	Each
Axles	25K Oil Bath	3	Std
Suspension	25,000 lb Heavy Duty 3 Leaf Springs	3	Axle
Suspension	49" Spread (Spring), 9700 Hutch	1	Std
	Standard trailer length and axle spread only allows for 2% unladen tongue		
	transfer. It is suggested that first axle air ride / lift is added for safe operation		
Suspension	while trailer is being towed empty	1	Std
Tires & Wheels	235/75R 17.5 J, 8 Bolt [17.5 x 6.75] Hub Pilot	12	Std
Hitch Length	Center of Coupler to Headboard, Appx	6.3	Feet
Hitch Type	3" Adjustable Lunette Eye/Pintle, [C] 90,000 lb (7/8" Gr 8 Bolts)	1	Std
Jack	140,000 lb Twin 2 Speed (39,000 lb Lift Capacity)	1	Pair
Lights	LED Lights (Peterson), Sealed Wiring Harness (Sealco)	1	Std
Plug	7 Pole Semi	1	Std
Standard	5/8" Safety Chains, Grade 80	1	Std
	Toolbox, Extended as far forward as possible (with lockable latch) in a-frame		
Standard	area of hitch	1	Std
Standard	Document Holder	1	Opt
Standard	2 Steps, 1 on the Standard Hitch and 1 in front of Axles on Roadside	2	Std
Trailer Color	Felling Black # CCA945378 (White Felling Decal)	1	Std
Stripe Color	White	1	Std
GVWR	63,000 lbs	1	Std