## Product Sheet Felling Trailers, Inc. 2025 www.felling.com • 1-800-245-2809

1525 Main Street South Sauk Centre, MN 56378

FT-60-4 LP Paver Paver Series

**GVWR LBS: 72,700 GAWR LBS: 18,160 WEIGHT LBS: 16,500 CAPACITY LBS: 56,200** 

| Feature Name     | Standard Features  | Std. Qty | UOM    |
|------------------|--|----------|--------|
| Model            | FT-60-4 LP Paver   | 1        |        |
|                  | Engineered Fabricated Hi-Tensile Grade 80 Main Frame Beams with Grade 80               |          |        |
| Frame Type       | Jr-I Cross-Members   | 1        | Std    |
| Deck Length      | Add Main Deck Length (Pierced Frame)   | 28       | Feet   |
| Deck Type        | White Oak 2" Nom   | 1        | Std    |
| Beavertail       | Wood Inlaid Beavertail   | 6        | Feet   |
| Beavertail, Acc  | Double Incline Double Incline  | 1        | Opt    |
|                  | 45" Wide x 11' (7.5'+3.5') Bi-Fold, Air Operated, Wood Inlaid (Includes 3 large        |          |        |
| Ramps; Rear      | air tanks & Bolt on Ramp Legs)   | 1        | Pair   |
| Appx Deck Height | 33" Loaded, 35" Unloaded   | 1        | Inches |
| Width            | 102"OD   | 32       | Feet   |
| Tie Downs        | D-Rings, 1" ** Straight ** (One Set Centered on BVT)                                   | 20       | Each   |
| Brakes           | Air, ABS 2S/1M, (Parking brakes on all axles)  | 1        | Each   |
| Axles            | 25K Oil Bath   | 4        | Std    |
| Suspension       | 49" Spread (Spring), 9700 Hutch  | 1        | Std    |
|                  | Standard trailer length and axle spread only allows for 2% unladen tongue              |          |        |
|                  | transfer. It is suggested that first and second axle air ride / lift is added for safe |          |        |
| Suspension       | operation while trailer is being towed empty   | 1        | Std    |
| Tires & Wheels   | 215/75R 17.5 H, 8 Bolt [17.5 x 6.75] Hub Pilot   | 16       | Std    |
| Hitch Length     | Center of Coupler to Headboard, Appx   | 6.3      | Feet   |
| Hitch Type       | 3" Adjustable 90K Pintle [C] (7/8" Gr 8 Bolts)   | 1        | Std    |
| Jack             | 140,000 lb Twin 2 Speed (39,000 lb Lift Capacity)                                      | 1        | Pair   |
| Lights           | LED Lights (Peterson), Sealed Wiring Harness (Sealco)                                  | 1        | Std    |
| Plug             | 7 Pole Semi  | 1        | Std    |
| Option           | (4) Axle Legality per State is Responsibilty of Dealer/ Customer                       | 1        | Std    |
| Trailer Color    | Felling Black # CCA945378 (White Felling Decal)  | 1        | Std    |
| Stripe Color     | White  | 1        | Std    |
| Standard         | 5/8" Safety Chains, Grade 80   | 1        | Std    |
|                  | Toolbox, Extended as far forward as possible (with lockable latch) in a-frame          |          |        |
| Standard         | area of hitch  | 1        | Std    |
| Standard         | Document Holder  | 1        | Opt    |
| Standard         | 2 Steps, 1 on the Standard Hitch and 1 in front of Axles on Roadside                   | 2        | Std    |
| GVWR             | 72,700 lbs   | 1        | Std    |